

strada s



STRADA S designed for and by baristas

AVAILABLE CONFIGURATIONS

no. groups:

configurations: AV | ABR

Over the course of two years La Marzocco worked with 30 of the world's finest coffee professionals to design a machine. This group was known as the Street Team. The Strada, Italian for "street," was named in their honor.

A lower profile invites customer engagement in a café setting, while also providing the barista an open, expansive work area. The Strada platform has been designed to encourage creativity and customization so that each machine can be unique.

STRADA S HIGHLIGHT

auto brew ratio / drip prediction

Incorporated scales improve beverage consistency by stopping extraction based on mass, while Drip Prediction uses an algorithm to improve shot accuracy.

FEATURES

proportional steam valve

Lever-style activation for proportional solenoid steam valve.

pro touch steam wands

High performing steam wands that are cool to the touch.

integrated scales (ABR only)

Precision scales built into the drip tray provide an improved level of consistency.

insulated boiler

Reduce energy consumption while contributing to temperature stability.

customization

The Strada platform has been designed to encourage creativity and customization so that each machine can be unique. The Strada is available in 2 different configurations to meet the specific needs of baristas and cafes around the world.

| SPECIFICATIONS | 2 group | 3 group |
|--------------------------------------|----------------------------------------|-----------------------|
| dimensions (W \times D \times H) | 32.7" x 27.2" x 19.7" | 40.6" x 27.2" x 19.7" |
| weight (lbs) | 169 | 206 |
| voltage (VAC, phase, Hz) | 220, 1 | 220, 1 |
| element wattage | 4330—5666 | 5830—7783 |
| steam boiler capacity (liters) | 8.2 | 11.8 |
| brew boiler capacity (liters) | 2.6 | 3.9 |
| amp service required | 30 | 50 |
| certifications | UL-197, NSF-8, CAN / CSA-C22.2 No. 109 | |